

产品及应用PRODUCTS APPLICATIONS

- ▲ 机床控制变压器是参考德国西门子公司样机制造的新产品，符合VDE0550、IEC204-1、IEC439、GB5226-85等有关国际、国家标准。机床控制变压器适用于在交流50Hz-60Hz，输入额定电压不大于500V，额定输出电压不大于220V，作为各行业的机械设备，一般电器的控制电源和工作照明、信号灯的电源之用
- 
- ▲ The machine tool control transformer is a new product manufactured by referencing the samples of Siemens AG, Germany. It complies with relevant international and national standards such as VDE0550, IEC204-1, IEC439, and GB5226-85. The machine tool control transformer is suitable for use as a control power source for various industries' mechanical equipment and general electrical appliances, as well as a power source for work lighting and signal lamps, with an AC frequency of 50Hz-60Hz, an input rated voltage not exceeding 500V, and an output rated voltage not exceeding 220V.

技术参数SPECIFICATION

1. 额定容量：25VA~5000VA

3.环境温度：-15℃~+40℃

5.输出电压：6V/6.3V/12V/24V/36V/48V/110V/127V/220V/380V
- 2.输入电压：380V 220V 110V

4.工频耐压：3KV/min
1. Rated capacity: 25VA~5000VA

3.Ambient temperature: -15℃~+40℃

5.Output voltage: 6V/6.3V/12V/24V/36V/48V/11V/127V/220V/380V
- 2.Input voltage: 380V 220V 110V

4.Power frequency withstand voltage: 3KV/min

型号 Models	容量 VA Capacity	重量 kg Weight	外形尺寸 External dimensions			安装尺寸 Installation dimensions		安装孔 Mounting holes
			L	W	H	A	B	
YBK3-40	40	1.2	78	72	89	56±0.4	51±2.5	4.8×9
YBK3-50	50	1.3	78	72	89	56±0.4	51±2.5	4.8×9
YBK3-63	63	1.3	78	72	89	56±0.4	51±2.5	4.8×9
YBK3-80	80	1.8	84	105	94	64±0.4	66±2.5	4.8×9
YBK3-100	100	2.1	84	105	94	64±0.4	66±2.5	4.8×9
YBK3-125	125	2.5	96	105	109	84±0.4	71±3	5.8×11
YBK3-160	160	2.8	96	105	109	84±0.4	71±3	5.8×11
YBK3-200	200	3.2	96	120	109	84±0.4	86±3	5.8×11
YBK3-250	250	3.5	96	120	109	84±0.4	86±3	5.8×11
YBK3-315	315	4.4	120	109	123	90±0.4	90±2	7×12
YBK3-400	400	4.9	120	109	123	90±0.4	90±2	7×12
YBK3-500	500	6.2	150	112	150	122±0.5	90±3.5	7×12
YBK3-630	630	7.2	150	112	150	122±0.5	90±3.5	7×12
YBK3-800	800	10	160	210	151	126±2	152±2	7×12
YBK3-1000	1000	12.5	160	210	151	126±2	152±2	7×12
YBK3-1250	1250	15.2	184	235	163	146±3.5	176±3.5	7×12
YBK3-1600	1600	21.5	184	235	163	146±3.5	176±3.5	7×12
YBK3-2000	2000	25.5	210	265	171	174±3.5	200±3.5	7×12
YBK3-2500	2500	28	210	265	171	174±3.5	200±3.5	7×12

外型尺寸HOUSING AND DIMENSIONS: (MM)

